

DSP Flexipower



DSP

0.9

4

THD

EPO
/

RS485

50 /60

- UPSMAN

-
-
-

USB

: Net agent Mini DY 522 & CS141BL

-

1000W

5-6-8-10

-

00 10 20 30 40 50 60

DSP Flexipower -

	FP1105	FP1106	FP1108	FP1110	FP3110
()	5	6	8	10	10
()	4,5	5,4	7,2	9	9
	1Ph + N + PE				3Ph + N + PE
	220V/230/240V				380V/400V/415V
	180 V				320 V
	280 V				485 V
	45 - 65 Hz				
	0,99				
	0,9				
	1Ph + N + PE				
	220V / 230V / 240V ()				
THD	<3%				
	50 Hz 60 Hz ()				
()	±0,2 %				
(0-100%)	<1%				
-	3:1				
	0				
	2	100% - 120%			
	30	120% - 150%			
	150%				
	≥92%				
	-				
()	4-6	90%			
	20	12V			
	240VDC				
()	7	/ 9			
	Line	Back up	Ecomode,	/	
				%	
				24	
()	RS232	RS485,	SNMP,		
	0 °C... + 40 °C				
	20 - 25 °C				
	95% ()				
1	<50 dB			<52 dB	
	IP 20				
	585x254x710				
()	30	38	45		
	E N50091 - 1 EN50091 - 2 EN62040 - 3, EN50091 - 3 CE, , ISO				